ARITCO COMPACT LIFT





M ORGAN ELLIS

ARITCO COMPACT LIFT


LIFT DOORS

The lift doors are manual swing doors as standard, with the option to upgrade to automatic double doors.

LIFT COLOUR



DESIGNWALL



LIFT GLASS



LIFT FLOOR



CARRIER AND CONTROL PANEL

The carrier includes an L-shaped platform and a DesignWall that moves with you. The lift is operated via the central control panel on the DesignWall.

2248 MM

TOP HEIGHT

INSTALLATION

Recessed installation 50mm below floor or installed directly on the floor with a ramp.

TYPE OF LIFT

Home lift intended for installation in private homes.

Only to be used in buildings without public access.

RATED SPEED

0.15 m/s Inside Europe

DRIVE SYSTEM

Patented screw and nut system

2 to 6 floors



WARRANTY

The screw and nut assembly has a 10 year warranty.



CONTROL FROM CARRIER CONTROL PANEL

Hold to run – press and hold

POWER SUPPLY 230 V L-phase 20 POWER


230 V I-phase 20 amp C-Breaker



TECHNICAL COMPLIANCE

European Machine directive 2006/42/EC European standard EN 81-41






Carrier size: 580 × 805 mm External dim.: 840 × 880 mm Rated load: 250 kg / 2 persons



Carrier size: 880 × 805 mm External dim.: 1140 × 880 mm Rated load: 250 kg / 2 persons



Carrier size: 1080 x 805 mm External dim.: 1340 x 930 mm Rated load: 250 kg / 2 persons

MORGANELLIS.CO.UK | ENQUIRIES@MORGANELLIS.CO.UK | 01702 780002 SHOWROOM: SKY HOUSE DESIGN CENTRE, RAANS RD, AMERSHAM, HP6 6FT